



## Alitherm Heritage HD

Alitherm Heritage HD is designed to provide a solution where heritage projects require a larger opening sash size than offered by a standard Alitherm Heritage casement window.

The Alitherm Heritage range is designed to meet the needs of refurbishment and renewal projects, particularly in sensitive planning areas. Ideal for Victorian, Edwardian and Art Deco projects, its range of windows is proven in a wide range of renovation, refurbishment and heritage projects across the UK, providing a modern, high-performance replacement for traditional steel windows and doors.

- Offers larger opening sash sizes
- 1.5 W/m<sup>2</sup>K (using sealed unit 1.0 W/m<sup>2</sup>K)
- WER B

Smart are the UK's leading supplier of window and door systems. With over 40 years' experience, we take great pride not only in the quality, breadth and depth of our product range, but also in our design expertise and support services. To find out more about our products visit www.smartsystems.co.uk.

















# Alitherm Heritage HD

Suitable for side hung, top hung and fixed windows, Alitherm Heritage HD features the same traditional aesthetics and slim sightlines the range is recognised for. The system incorporates Sterling hinges and new longer locking rods that allow opening sash sizes to be increased to meet the specified requirements of individual projects.

Our Alitherm Heritage ranges are available with a full suite of hardware options, with products specifically designed to match window furniture that is synonymous with Victorian and Art Deco styles – including 'Monkey Tail' and 'Bulb' options.



#### Application

- Fixed Windows
- Side hung open out casements
- Top hung open out casements

#### Features

- Polyamide thermal break provides enhanced thermal performance
- Designed as a direct replacement for steel windows
- A range of high quality modern, traditional and Art-Deco hardware is available


#### Finish

Single or dual colour, marine quality powder coat as standard

### Technical Performance

WER	WER Rating B				
U Value	U Value 1.5 W/m²K (using sealed unit 1.0 W/m²K)				
Dimensions					
Frame Depth	52mm				
Glass	24mm, 28mm, 32mm & 42mm (depending on section selection)				
Document L Compliant					
Test Certification					
Security	PAS24: 2016				





Window Type	Maximum Width (mm)	Maximum Height (mm)	Maximum Weight (kg)	Air Permeability Classification	Watertightness Classification	Resistance to Wind Classification	
For sizes outside these parameters, contact the Smart Technical Support team. Design limitations tested to PAS 24 are noted below. Maximum design limitations outside of these dimensions are in the process of being tested.							
Side Hung (Tested to PAS 24)	600	1400	40	Class 4	Class 7A	Class AE2400	
Side Hung	838 <sup>4</sup>	1750 <sup>₿</sup>	55	ТВА	ТВА	ТВА	
Top Hung (Tested to PAS 24)	1400	1300	40	Class 4	Class 7A	Class AE2400	
Top Hung	1750 <sup>₿</sup>	2500 <sup>4</sup>	180	ТВА	ТВА	ТВА	

A. Subject to profile selection and further testing.

B. New espagnolette required. Check availability.

Smart Systems Limited Arnolds Way, Yatton, Bristol Somerset, BS49 4QN. UK

IMS608AHD.202006

**T** +44 (0)1934 876 100 **F** +44 (0)1934 835 169

www.smartsystems.co.uk

The images, drawings and data shown in this brochure are for illustrative purposes only and are not binding in detail, colour or specification. We reserve the right to make changes to the product specification as technical developments dictate and without prior notice. We recommend that the user ensures that they are satisfied the product meets their requirements prior to purchase. ©Smart Systems Ltd 2020